

Marking and Labeling System Materials - Component

COMPANY

KOSTIC FORMTEC CO.,LTD.

120 LG-ro 360beon-gil Wollong-myeon

Paju-si, Gyeonggi-do 10844 Republic of Korea

MH15817

Pressure-sensitive overlaminations:

Model No.	Type of Label Stock	Min Temp (°C)	Max Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
LAMI-1000						
	Polyester	-23	80	X	X	-
	Polypropylene	-23	60	X	X	-
LAMI-4000						
	Polyester	-23	80	X	X	-
	Polypropylene	-23	60	X	X	-

Pressure-sensitive unprinted label stocks:

Model No.	Application Surface	Min Temp (°C)	Max Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
KBSP						
	Epoxy paint	-20	100	X	-	-
	Acrylonitrile butadiene styrene	-20	80	X	-	-
	Polypropylene	-20	60	X	-	-
KMSP						
	Epoxy paint	-20	100	X	-	-
	Acrylonitrile butadiene styrene	-20	60	X	-	-
	Polypropylene	-20	60	X	-	-
KNY						
	Acrylonitrile butadiene styrene	-20	60	X	-	-
	Epoxy paint	-20	60	X	-	-

	Galvanized steel	-40	60	X	-	-
	Polypropylene	-20	60	X	-	-
KWP						
	Epoxy paint	-20	100	X	-	-
	Acrylonitrile butadiene styrene	-20	60	X	-	-
	Polypropylene	-20	60	X	-	-
KWP-1						
	Aluminum	-20	80	X	-	-
	Stainless steel	-20	80	X	-	-
MSP						
	Epoxy paint	-23	100	X	-	-
	Acrylonitrile butadiene styrene	-23	60	X	-	-
	Polypropylene	-23	60	X	-	-

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

Marking: Company name and model designation.

Last Updated on 2022-11-18

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."